

CP-UNR-4K5324-V3

32 Ch. 4K Network Video Recorder

- Up to 32 Channels IP camera input
- AI disabled: 256 Mbps incoming, AI enabled: 180 Mbps incoming
- Instastream, H.265, H.264+, H.264, MJPEG Decoding
- AI by Camera: Face detection, Face recognition, Perimeter protection, IMD+, ANPR, People counting, Stereo analysis, Heat map
- AI by NVR: Face detection, Face recognition, Perimeter protection, IMD+
- Up to 16MP Video Resolution
- Support 4 SATA ports, up to 16TB, 2 USB (1 front USB 2.0 Port, 1 rear USB 3.0 Port)
- 1 HDMI, 1 VGA simultaneous video output
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro Lite



System Overview

This NVR has gathered momentum across the globe for its outstanding performance and premium recording quality as it can be applied in any situation for IP video surveillance. This Series of NVRs supports the input, recording and transmission functions. Along with that, this NVR also enjoys the help of a built-in deep learning module as this product adopts the video image that is structured on deep learning algorithms. This NVR lets you achieve high-precision human face-recognition and efficient perimeter protection.

This product has been crafted to pay attention to what matters the most through applying deep learning artificial intelligence, which makes it fasten the event response time and helps in making the video more actionable.



CP-UNR-4K5324-V3

32 Ch. 4K Network Video Recorder

Functions

Face Recognition

This technology can be used to extract faces from a range of cameras and is capable of processing large quantities of faces in real-time or post-event and can provide alerts to help with access and authentication, border security, and crowd control.

Instastream

This camera has been designed with the latest and most efficient innovation among the standard video compression designs. Smart encoding algorithms developed by CP PLUS help in saving up to 70% more bandwidth than H.265 along with making it more beneficial for minimizing bandwidth and storage costs. It enhances video coding efficiency while providing high resolution and the rate of frame in the video using Intelligent Region Perception to detect motion in each frame.

gCMOB/ iCMOB

Designed to allow users to access and control live streaming from CP PLUS IP Cameras, DVRs/ NVRs and Video Door Phones, the CP PLUS gCMOB/ iCMOB application offers a host of features such as Easy GUI, up to 16 live viewing split-ups; InstaOn cloud support; Playback; digital zoom ins; two-way talk, and more.

Face Detection

With the help of the deep learning algorithm that is used in this technology, people can easily be detected, tracked, recorded, and captured. It takes only a second to detect one human face. Face detection is useful in cameras to help with auto-focus. This technology is mainly used to identify the presence of a human face.

Intelligent Motion Detection (IMD+) by Camera

IMD+ in CP PLUS NVRs intelligently identifies real movement in the scene by distinguishing humans and vehicles from background noise such as light changes, rain, or moving leaves. This helps reduce false alarms and ensures that only important security events are recorded and notified. The system analyses the video in real time and accurately detects activity within defined areas. This makes surveillance smarter, more reliable, and easier to manage for both home and business users.

KVMS Pro Lite

The KVMS Pro Lite is a hybrid security management software that allows the management of various surveillance devices such as cameras, DVRs/ NVRs, encoders/ decoders, etc. It is released with the surveillance hardware and exclusively supports CP PLUS devices.

About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure



CP-UNR-4K5324-V3

32 Ch. 4K Network Video Recorder

Feature	Specification
Processor	Industrial-grade processor
IP Camera Input	32 Channels
Operating System	Embedded LINUX
User Interface	Web, Local GUI
AI by Camera	Face detection, Face recognition, Perimeter protection, IMD+, ANPR, People counting, Stereo analysis, Heat map
AI by NVR	Face detection, Face recognition, Perimeter protection, IMD+
Perimeter Performance AI by NVR	2 Channels, 10 IVS rules for each channel
Perimeter Performance of AI by Camera	Human and vehicle detection on all channels, supporting up to 8 targets per second
Face Detection AI by NVR	1 Channel (up to 12 face images/s each Channel)
Video Output	1 HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720; 1 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720
Face Attributes	Gender, Age group, Glasses, Expressions, Face mask, Beard
Abnormality Alarm	Camera disconnection, Storage error, Disk full, IP Conflict, MAC conflict, Login locked and Cybersecurity exception
Face Database Capacity	Up to 10 face databases with 200,00 images, with a total capacity of 2.5 G. Name, gender, birthday, address, credential type, credential No., countries & regions and state can be added to each face image
IMD+ by NVR	4 Channels: Secondary filtering for human and motor vehicle, reducing false alarms caused by leaves, rain and lighting condition change
Face Recognition AI by NVR	8 Channels FD (by camera) + FR (by recorder), image Stream: 12 face images/s 1 Channel FD (by recorder) + FR (by recorder), video Stream: 12 face images/s
Face Recognition AI by Camera	Human and vehicle detection on all channels, supporting up to 8 targets per second
Face Detection AI by Camera	Human and vehicle detection on all channels, supporting up to 8 targets per second

Feature	Specification
Network Bandwidth	AI disabled: 256 Mbps incoming, 256 Mbps recording and 256 Mbps outgoing AI enabled: 180 Mbps incoming, 180 Mbps recording and 180 Mbps outgoing
Video Compression	Instastream, H.265, H.264+, H.264, MJPEG
ANPR by Camera (Number of Channels)	8 Channels
Video Display Split	Main screen: 1/4/8/9/16/25/36 Sub screen: 1/4/8/9/16
Decoding Capability	AI disabled: 2 Channels 16MP@30 fps, 2 Channels 12MP@30 fps, 4 Channels 8MP@30 fps, 6 Channels 5MP@30 fps, 8 Channels 4MP@30 fps, 16 Channels 1080p@30 fps AI enabled: 1 Channel 16MP@30 fps, 2 Channels 12MP@30 fps, 3 Channels 8MP@30 fps, 4 Channels 5MP@30 fps, 6 Channels 4MP@30 fps, 12 Channel 1080p@30 fps
Record Mode	General, Motion detection, Intelligent, Alarm
License Plate Database Capacity	1. Create up to 20,000 plate numbers 2. Blocklist and allowlist
Resolution	16MP, 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 2MP, 960p, 720P, D1, CIF
Disk Group	Support
Hard Disk	4 SATA ports, up to 16 TB. The maximum HDD capacity varies with environment temperature
General Alarm	Motion detection, Privacy masking, Video loss, Scene Changing, PIR alarm, IPC external alarm
Intelligent Alarm	Face detection, Face recognition, Perimeter protection, IMD+, People counting, Stereo analysis, Heat map
Alarm Linkage	Record, Snapshot, IPC external alarm output, Audio, Buzzer, Log, Preset, Email
Playback Mode	Instant playback, General playback, Event playback, Tag Playback, Smart layback
Multi-Channel Playback	Up to 16 Channels
Interface Ports	2 (1 front USB 2.0 port, 1 rear USB 3.0 port), 1 HDMI, 1 VGA, 1 RS232, 1 RS485
Ethernet	2 (10/100/1000 Mbps Ethernet port, RJ-45)
Protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, InstaOn, Auto Connect, ONVIF (Profile T, Profile S, Profile G), CGI, SDK
IMD+ by Camera	8 Channels
Backup Method	USB device and network

Feature	Specification
Alarm Input	16 Channels
Alarm Output	4 Channels
Audio Compression	G.711a, G.711u, PCM, G726, AAC
Audio Input	1 Channel RCA
Audio Output	1 Channel RCA
Smart Phone	iPhone, iPad, Android Phone
Browser	Chrome, IE9 and later, Firefox
Power Supply	100–240 VAC, 50-60Hz
Power Consumption	<10 W (without HDD)
Operating Temperature	–10 °C to +55 °C (14 °F to +131 °F)
Operating Humidity	10%–93% (RH)
Storage Temperature	–20 °C to +60 °C (–4 °F to +140 °F)
Dimensions	440.0 mm × 415.6 mm x 76.0 mm
Weight	4250g

Published Date –22-06-2026

Company Name:

CP PLUS (Aditya Infotech Ltd.)

F-28 Okhla Industrial Area, Phase 1,

New Delhi 110020, INDIA

Contact Mail ID :- customercare@cpplusworld.com