

CP-UNC-DA81L3C-LQ

8MP Dual Light Dome Camera - 30Mtr.

- 1/2.7" 8MP PS CMOS Image Sensor (0.9407 centimeters)
- Max. 8MP (3840 × 2160)@1–20 fps
- Instastream, H.265, H.264, H.264H, H.264B, MJPEG
- Support Triple stream
- DWDR, Day/Night(ICR), 2D NR, 3D NR, ROI, AWB, AGC, BLC, HLC, Digital watermarking
- IR Range of 30 Mtr., Warm Light Range of 30 Mtr.
- 3.6mm Lens
- Support Built-in Mic, PoE, IP67
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro Lite, EVMS Pro



iiuMAX
Dual Light

System Overview

The CP PLUS Advanced Dual Light Cameras provide the perfect solution for elevating your security system. Designed for superior adaptability, these cameras support multiple illumination modes and advanced monitoring features, ensuring unmatched performance in various environments.

CTC Technology:

CP PLUS Trusted Core Technology is a multi-layered security architecture that brings together the best of cyber security practices and technological intelligence. It is not just an enhancement; it is a complete redefinition of how surveillance should function in today's digital landscape - more intelligent, more secure, and more reliable than ever before.



CP-UNC-DA81L3C-LQ

8MP Dual Light Dome Camera - 30Mtr.

Functions

Instastream

This camera has been designed with the latest and most efficient innovation among the standard video compression designs. Smart encoding algorithms developed by CP PLUS help in saving up to 70% more bandwidth than H.265 along with making it more beneficial for minimizing bandwidth and storage costs. It enhances video coding efficiency while providing high resolution and the rate of frame in the video using Intelligent Region Perception to detect motion in each frame.

Regions of interest

Regions of Interest (ROI) is a user defined feature that allows the operator to monitor specific areas of a scene while still maintaining overall situational awareness of less important areas.

True Day/Night

When the scene is too dark, the image is captured by illuminating an infrared light through the camera onto the scene that greatly helps with making the scene visible for the lens. It delivers color images during the day and automatically switches to the monochrome feature as the scene darkens.

Power over Ethernet (PoE)

CP PLUS cameras with Power over Ethernet (PoE) technology offer a simple and efficient installation by using a single Ethernet cable to deliver both power and data. This eliminates the need for separate power adapters, reduces cable clutter, and ensures a cleaner setup.

About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



CP-UNC-DA81L3C-LQ

8MP Dual Light Dome Camera - 30Mtr.


Feature	Specification
Image Sensor	1/2.7" 8MP PS CMOS Image Sensor (0.9407 Centimeters)
Effective Pixels	3840 (H) × 2160 (V)
Minimum Illumination	0.001 lux@F1.4 (Color, 30 IRE), 0.0001 lux@F1.4 (B/W, 30 IRE), 0 lux (IR on)
Angle Adjustment	Pan: 0°–360°, Tilt: 0°–78°, Rotation: 0°–360°
Shutter Speed	Auto/Manual 1/3 s–1/100,000 s
White Balance	Auto, Natural, Street lamp, Outdoor, Manual, Regional custom
RAM	256 MB
ROM	128 MB
DORI Distance	98.7 m (Detect), 39.5 m (Observe), 19.7 m (Recognize), 9.9 m (Identify)
Gain Control(AGC)	Auto/ Manual
Lens Type	Fixed-focal
Max. Aperture	F1.4
Close Focus Distance	1.9 m
Lens Mount	M12
Lens	3.6mm Lens
Video Compression	Instream, H.265, H.264, H.264H, H.264B, MJPEG (Only supported by the sub stream)
S/N Ratio	>56dB
IR Number	1 (Multi-core (IR + warm) light)
IR	IR Range of 30 Mtr.
Warm Light	Warm Light Range of 30 Mtr.
Day/Night	Auto(ICR)/Color/B/W
Angle of View	H: 86°, V: 49°, D: 100°
Back Light Compensation	BLC/ HLC/ DWDR
OTA (Over-The-Air)	Support

Feature	Specification
Stream Capability	Triple stream
Frame Rate	Main stream: 8MP (3840 × 2160)@1-20fps, 6MP (3072 × 2048)@1-20fps, 5MP (3072 × 1728)@1-20fps, 4MP (2880 × 1620/ 2688 × 1520)@1-25/30fps, 3MP (2048 × 1536/2304 × 1296)@1-25/30fps, 2MP (1920 × 1080)@1-25/30fps, 1.3MP (1280 × 960)@1-25/30fps, 720p (1280 × 720)@1-25/30fps Sub Stream 1: D1 (704 × 576/ 704 × 480)@1-25/30fps, VGA (640 × 480)@1-25/30fps, CIF (352 × 288/ 352 × 240)@1-25/30fps Sub stream 2: D1 (704 × 576/ 704 × 480)@1-25/30fps, VGA (640 × 480)@1-25/30fps, CIF (352 × 288/ 352 × 240)@1-25/30fps *The sub streams max. frame rates depends on main stream frame rates
Smart search	Work together with CP Plus AI NVR to perform refine AI search, event extraction and merging to event videos
Video format	PAL/NTSC
Privacy Mask	4 areas
ROI	Support (4 areas)
OSD	Privacy Masking, Channel Title, Time Title, Location, Font Properties, Custom Title
Audio	Built-in Mic
Audio Compression	G.711a, G.711Mu, PCM, G.726, AAC
Bit Rate	H.265: 3 kbps–8192 kbps, H.264: 3 kbps–8192 kbps
Bit Rate Control	CBR/VBR
Protocol	SFTP, IPv6, IPv4, DNS,RTCP, NTP, RTP, HTTP, HTTPS, SNMP V3, TCP/IP, PPPoE, NFS, UPNP, UDP, ICMP, SSL, DHCP, SMTP, RTSPS, ONVIF (Profile S, Profile G, Profile T), unicast, multicast, TLS 1.2, 1.3, InstaOn
SDK and API	Support
Ethernet	RJ-45 (10/100 Base-T)
Resolution	8MP (3840 × 2160), 6MP (3072 × 2048), 5MP (3072 × 1728), 4MP (2880 × 1620/2688 × 1520), 3MP (2048 × 1536/2304 × 1296), 2MP (1920 × 1080), 1.3MP (1280 × 960), 720p (1280 × 720), D1 (704 × 576/704 × 480), VGA (640 × 480), CIF (352 × 288/352 × 240)
Noise Reduction	2D NR, 3D NR
Motion detection	OFF/ON (4 areas, rectangular)
Cyber Security	AES 256-bit Encryption, Configuration encryption, trusted execution, Digest, security logs, WSSE, account lockout, syslog, video encryption, IP/MAC filtering, HTTPS, trusted upgrade, trusted boot
IMD	Support the classification and accurate detection of human and vehicle
Mirror Function	Support
IR Control	Auto, Manual

Feature	Specification
Iris Control	Fixed
Storage	SFTP, NAS
Smart IR	Support
Image Rotation	0°/90°/180°/270° (Support 90°/270° with 2688 ×1520 resolution and lower)
Alarm Event	Network disconnection, IP conflict, illegal access, Motion detection, Video tampering, Audio detection, IMD (Intelligent motion detection), Security exception
User/Host	6 (Total bandwidth: 48 M)
Browser	IE, Chrome, Firefox, Microsoft Edge
Certificates	ISO 9001: 2015, ISO 20000-1 : 2018, CE, FCC and RoHS, BIS, STQC approved compliance report
Power Source	12 VDC/PoE (802.3af)
Power Consumption	Basic: 2.5 W (12 VDC), 3.5 W (PoE) Max.: 4.5 W (12 VDC), 5.8 W (PoE) (H.265 + intelligence on+ DWDR + illuminator intensity)
Weatherproof Standard	IP67
Operating Temperature	–40°C to +55°C
Operating Humidity	≤95% (RH), non-condensing
Storage Temperature	–40°C to +60°C
Storage Humidity	≤95%(RH), non-condensing
Dimension	85.6 mm × 94.0 mm
Casing	Metal + Plastic
Weight	280g

Published Date –09-07-2026

Dimensions (mm/inch)



Company Name:

CP PLUS (Aditya Infotech Ltd.)

F-28 Okhla Industrial Area, Phase 1,

New Delhi 110020, INDIA

Contact Mail ID :- customercare@cpplusworld.com